
FreeSpeak II 2.4 GHz Transceiver Antenna

FreeSpeak II Wireless Solutions



Key Features and Benefits

- Functions with FSII base, FreeSpeak Edge base, Arcadia Central Station, E-IPA-HX cards, and FSII splitter hardware
- Supports 4 FSII-BP24 beltpacks per FSII-TCVR-24 transceiver
- Supports systems with up to 40 beltpacks
- Blue LED status indicator on top and bottom
- Mic stand or wall mount orientation (metric and imperial threads)
- IP53 rating for wet and dusty conditions

FreeSpeak II[®] is a high performance wireless solution operating in the 2.4 GHz frequency bands designed for extensive communication in large-scale operations.

Description

The FSII-TCVR-24 is an active transceiver antenna for the FSII-BP24 beltpacks. The transceiver can be locally powered or powered via the FSII base station or matrix on shorter connections (less than 1000 ft). The FSII-TCVR-24 has a mount for wall or microphone stand. A blue status light is visible from either mounting orientations.

Durability

The FSII-TCVR-24 is IP53 rated for wet weather or dusty conditions making them ideal for outdoor productions.



FreeSpeak II 2.4 GHz Transceiver Antenna

FreeSpeak II Wireless Solutions

Technical Specifications

Frequency Spectrum: 2.400-2.483GHz for EU and US Cellular auto

roaming technology

Modulation: GFSK, TDMA frame 10ms Full slot Output power (EU): 18dBm, (RoW): 22dBm

Environmental

IP53 water and dust resistance -67° to +158°F (-55° to +70°C)


Dimensions

7 x 5.7 x 2in (HxWxD) (178 x 144.8 x 51mm)

Weight

15.7oz (0.45kg)

FSII-TCVR-24 Bottom Panel



Legend

- 1. USB (factory use)
- Ethercon RJ45 (base/matrix connection)
- DC In
- 4. Mode Button

Order Codes

FSII-TCVR-24: Transceiver approved for use in USA, Canada and world wide sales except EU

FSII-TCVR-24-EU: Transceiver approved for use in the EU



www.clearcom.com

trademarks of Clear-Com LLC.